





www.uniprize.co.uk
mail@uniprize.co.uk

UDAR 25/30/32/35/40/ 45 Column Drilling Machine

| MODEL | UDAR 25 | UDAR 30 | UDAR 32 | UDAR 35 | UDAR 40 | UDAR 45 |
|--|---------------------------------|---------------------------------|--------------------------------|--------------------------------|-----------------------------|-----------------------------|
| Drilling Capacity in Steel of 70kg | 25mm | 32mm | 32mm | 35mm | 40mm | 45mm |
| Tapping Capacity in Steel of 70kg | M.22 | M.25 | M.28 | M.30 | M.32 | M.35 |
| Transmission — Gears hardened and Grounded | ** | ** | ** | ** | ** | ** |
| Speed Number and Range (rpm) 50 Hz. | (8) 65 - 3060 | (8) 65 - 3060 | (8) 75 - 2100 | (8) 75 - 2100 | (8) 93 - 1420 | (8) 93 - 1420 |
| Speed Number and Range (rpm) 60 Hz. | (8) 78- 3672 | (8) 78- 3672 | (8) 90 - 2520 | (8) 90 - 2520 | (8) 112 - 1704 | (8) 112 - 1704 |
| Feed – Automatic ** | ** | ** | ** | ** | ** | ** |
| Number & Range of Feeds | (2) 0,10 – 0,20 | (2) 0,10 – 0,20 | (3) 0,10 - 0,20 - 0,30 | (3) 0,10 - 0,20 - 0,30 | (3) 0,10 – 0,18 – 0,24 | (3) 0,10 – 0,18 – 0,24 |
| Clutch – Mechanical (Automatic) ** | ** | ** | ** | ** | ** | ** |
| Main Motor Speed (rpm) | 1,500 / 3,000 | 1,500 / 3,000 | 750 / 1,500 | 750 / 1,500 | 1,500 | 1,500 |
| Spindle Cone | MT.3 | MT.3 | MT.4 | MT.4 | MT.4 | MT.4 |
| Spindle Stroke | 120mm | 120mm | 160mm | 160mm | 180mm | 180mm |
| Distance Spindle Column | 250mm | 250mm | 300mm | 300mm | 350mm | 350mm |
| Distance Spindle Table | Min 170mm – Max. 820mm | Min 170mm – Max. 820mm | Min 70mm – Max. 885mm | Min 70mm – Max. 885mm | Min 95mm – Max. 865mm | Min 95mm – Max. 865mm |
| Distance Spindle Base | 1,220mm | 1,220mm | 1,245mm | 1,245mm | 1,220mm | 1,220mm |
| Column Diameter | 100 | 100 | 125 | 125 | 150 | 150 |
| Table Dimensions | 270 x 300mm | 270 x 300mm | 400 x 420mm | 400 x 420mm | 480 x 480mm | 480 x 480mm |
| Base Dimensions | 665 x 400mm | 665 x 400mm | 492 x 655mm | 492 x 655mm | 480 x 755mm | 480 x 755mm |
| Table with "T" Slots ** | ** | ** | ** | ** | ** | ** |
| Depth Adjustable End ** | ** | ** | ** | ** | ** | ** |
| Coolant Equipment ** | ** | ** | ** | ** | ** | ** |
| Tool Ejector ** | ** | ** | ** | ** | ** | ** |
| Lighting Equipment ** | ** | ** | ** | ** | ** | ** |
| Main Switch | No | No | Yes | Yes | Yes | Yes |
| Switch Motor Guard ** | ** | ** | ** | ** | ** | ** |
| Emergency Push Button ** | ** | ** | ** | ** | ** | ** |
| Turning Sense Selector ** | ** | ** | ** | ** | ** | ** |
| Electrical Equipment at Low V ** | ** | ** | ** | ** | ** | ** |
| Drill Guard with Stop Micro ** | ** | ** | ** | ** | ** | ** |
| CE Norms ** | ** | ** | ** | ** | ** | ** |
| | 250 / 310 | 260 / 320 | 250 / 310 | 292 / 392 | 317 / 417 | 435 / 565 |

Optional Accessories:

- > Front Wheel for Fine Sensitive Feed
- > Speed Digital reading
- > Depth Digital Reading
- > Reversing for Tapping IR / RS
- > Automatic Tapping by Lead Screw with Braking Device (1 Spindle included)
- > Additional Lead Screw special pitch
- > Additional Lead Screw standard pitch
- > Rotating Table
- > 100 Reversible Fixed Table with Vice
- > Multispindle Headstock Adaptation
- > Multispindle Headstock Guiding
- > Column Supplement
- > Automatic Drilling Feed by Hydroblock
- > Multispindle Headstock Pneumatic Balancing
- > Cooling for Each Spindle of Multispindle Headstock
- > Cross Table with Fixed Support 100
- > Cross Table 430 XY (MS-204) Surface 430 x 240mm (X=280mm / Y = 180mm)
- > Bi Manual Command